


● **Features:**

- 1. Emitted color : Yellow (Amber)
- 2. Lens Appearance : Water Clear
- 3. Indoor and outdoor application.
- 4. Low power consumption.
- 5. Wet and dust proof.


● **Package dimensions**



Notes:

- 1. All dimensions are in millimeters.
- 2. Tolerance is ±0.3mm unless otherwise specified.
- 3. Lead spacing is measured where the leads emerge from the package.
- 4. Specifications are subject to change without notice.

● **Circuit Diagram**



● **Applications:**

- 1. Customer design.



STR2-16Y-80

● Absolute maximum ratings(Ta=25℃)

Parameter	Symbol	Rating	Unit
Power Dissipation	Pd	2.6	W
Vcc	Vcc	13	V
Peak Forward Current*1	I _{FP}	400	mA
Reverse Voltage	V _R	10	V
Operating Temperature	Topr	-25℃~60℃	
Storage Temperature	Tstg	-30℃~85℃	

*1Condition for I_{FP} is pulse of 1/10 duty and 0.1msec width.

● Electrical and optical characteristics(Ta=25℃)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Current	I _F	Vcc=12V	160	180	200	mA
Luminous Intensity	I _v	Vcc=12V	35		55	lm
Reverse Current	I _R	V _R =10V	-	-	180	μA
Color Rank		Vcc=12V	585~594			nm
Viewing Angle	θ _{1/2}	Vcc=12V	70	-----	80	deg